

## MRP List - June-2022



### Temperature Controllers

#### Temperature indicator

| Model   | Size (H X W X D)mm | MRP  | Item Description                              | HSN Code | GST Rate |
|---|--------------------|------|---|----------|----------|
| TI-11   | 96 X 96 X 42       | 1360 | Fixed input : J,K,Pt-100,<br>Supply : 230V AC | 90303390 | 18%      |
| TI-21   | 72 X 72 X 60       | 1360 |   |          |          |
| TI-31V  | 96 X 48 X 85       | 1495 |   |          |          |
| TI-41   | 48 X 48 X 70       | 1360 |   |          |          |
| UTI-38  | 48 X 96 X 67       | 1700 | Universal input :J,K,PT-100                   |          |          |
| <b>Note : For R &amp; S type input Extra on MRP</b> |                    | 325  |   |          |          |

#### Heater indicator

| Model    | Size (H X W X D)mm | MRP  | Item Description                                 | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| MHI-2024 | 72 X 72 X 75       | 1935 | 4 zone heater indicator                          | 90303390 | 18%      |
| MHI-2006 | 72 X 72 X 75       | 2220 | 6 zone heater indicator                          |          |          |
| MHI-2014 | 72 X 72 X 75       | 1935 | 4 zone heater indicator with separate aux supply |          |          |

#### Blind Temperature Controller

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| MCO-1501 | 96 X 96 X 55       | 1485 | Input : J type ,<br>Output : 1 relay,<br>control action : ON-OFF,<br>Supply : 230V AC | 90328910 | 18%      |
| MCO-2501 | 72 X 72 X 75       | 1485 |   |          |          |

### Temperature Controller With Knob

| Model    | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| MDC-11   | 96 X 96 X 55       | 1870 | Input : J/K/Pt-100(factory set) ,<br>Output : 1 relay,<br>control action : On-off,<br>Supply : 230V AC | 90328910 | 18%      |
| MDC-2911 | 72 X 72 X 75       | 1870 |  |          |          |

### Push to Set Temperature controller

| Model    | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| MDC-1901 | 96 X 96 X 100      | 2020 | Input : J/K/Pt-100(factory set),<br>Output : 1 relay,<br>control action : ON-OFF/TP (Factory set),<br>Supply : 230V AC | 90328910 | 18%      |
| MDC-2901 | 72 X 72 X 120      | 2020 |  |          |          |

### Blind Din rail PID Controller

| Model                 | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-----------------------|--------------------|------|--|----------|----------|
| DTC-1X(Master Module) | 76 X 27 X 116      | 2850 | Input : J/K/Pt-100(Configurable),<br>Output : 2 relay OR SSR + RS-485 Modbus<br>Control action : PID/TP/On-off (Configurable)<br>Supply : 24V DC | 90328910 | 18%      |
| DTC-1A(Slave module)  | 76 X 27 X 116      | 2850 |  |          |          |

| Cooling Controller |                    |      |   |          |          |
|--------------------|--------------------|------|---|----------|----------|
| Model              | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
| CC-5010            | 36 X 76 X 72       | 1375 | Input : NTC Sensor,<br>Output : 1Relay (10Amp),with auto defrost facility,<br>Supply : 230V AC OR 12V DC OR 24V DC                                  | 90328910 | 18%      |
| CC-5010T           | 36 X 76 X 72       | 1450 |   |          |          |
| CC-5020            | 36 X 76 X 72       | 1475 | Input : NTC Sensor,<br>Output : 1Relay (20Amp),with auto defrost facility,<br>Supply : 230V AC OR 12V DC OR 24V DC                                  |          |          |
| CC-5020T           | 36 X 76 X 72       | 1550 |   |          |          |
| CC-5052            | 36 X 76 X 72       | 2035 | Input : NTC Sensor,<br>Output : 2 Relay for Compressor<br>Supply : 230V AC OR 12V DC OR 24V DC  |          |          |
| CC-5012            | 36 X 76 X 72       | 1815 | Input : NTC Sensor,<br>Output : 1Relay (10Amp)+ 1 Alarm relay,<br>with auto defrost facility,<br>Supply : 230V AC OR 12V DC OR 24V DC               |          |          |
| CC-5015            | 36 X 76 X 72       | 1870 | Input : NTC Sensor,<br>Output : 1Relay (10Amp)+ 1 Alarm Buzzer ,<br>with auto defrost facility, With Buzzer<br>Supply : 230V AC OR 12V DC OR 24V DC |          |          |
| CC-5022            | 36 X 76 X 72       | 2035 | Input : NTC Sensor,<br>Output : 1Relay (20Amp)+ 1 Alarm Relay ,<br>with auto defrost facility, With Buzzer<br>Supply : 230V AC OR 12V DC OR 24V DC  |          |          |
| CC-5025            | 36 X 76 X 72       | 2090 | Input : NTC Sensor,<br>Output : 1Relay (20Amp)+ 1 Alarm Buzzer ,<br>with auto defrost facility, With Buzzer<br>Supply : 230V AC OR 12V DC OR 24V DC |          |          |
| CC-5021            | 36 X 76 X 72       | 2090 | Input : NTC Sensor,<br>Output : 1Relay (20Amp)+ 1 Relay for Heater ,<br>with auto defrost facility,<br>Supply : 230V AC OR 12V DC OR 24V DC         |          |          |

| Single Display Temperature Controller |                    |      |  |          |          |
|---------------------------------------|--------------------|------|--|----------|----------|
| Model                                 | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| TC-19                                 | 96 X 96 X 42       | 1430 | Input : J/K/Pt-100(factory set),<br>Output : 1 relay    SSR,   | 90328910 | 18%      |
| TC-29                                 | 72 X 72 X 60       | 1430 | Control action : On-off/Tp (Factory set),<br>Supply : 230V AC  |          |          |
| TC-49                                 | 48 X 48 X 70       | 1430 | Input : J/K (Configurable), Pt-100(factory set),<br>Output : 1 relay  SSR,<br>Control action : On-off/Tp (Configurable),<br>Supply : 100-270V AC |          |          |
| TC-39H                                | 48 X 96 X 75       | 1430 | Input : J/K/Pt-100(factory set),<br>Output : 1 relay,<br>Control action : On-off/Tp (Factory set),<br>Supply : 230V AC                           |          |          |

| Single Display PID Controller |                    |      |  |          |          |
|-------------------------------|--------------------|------|--|----------|----------|
| Model                         | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| TC-29P                        | 72 X 72 X 60       | 1485 | Input : J/Pt-100(factory set),<br>Output : 1 relay    SSR,<br>Control action : PID/Tp/On-off (Configurable),<br>Supply : 230V AC                   | 90328910 | 18%      |
| TC-49P                        | 48 X 48 X 70       | 1485 | Input : J/K (Configurable), Pt-100(factory set),<br>Output : 1 relay    SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC |          |          |

### Single Display Universal input PID Controller -3 Digit

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| UTC-413P | 48 X 48 X 70       | 1595 | Input : J/K/Pt-100(Configurable),<br>Output : 1 relay    SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC | 90328910 | 18%      |

### Single Display Universal input PID Controller -4 Digit

| Model   | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|---------|--------------------|------|---|----------|----------|
| UTC-114 | 96 X 96 X 50       | 1650 | Input : J/K/Pt-100(Configurable),<br>Output : 1 relay    SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC | 90328910 | 18%      |
| UTC-214 | 72 X 72 X 60       | 1650 |   |          |          |

### Double Display Universal input PID Controller single relay (3+3 Digit)

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| UTC-121P | 96 X 96 X 50       | 1935 | Input : J/K/Pt-100(Configurable),<br>Output : 1 relay  SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC | 90328910 | 18%      |
| UTC-221P | 72 X 72 X 60       | 1935 |   |          |          |
| UTC-421P | 48 X 48 X 70       | 1935 |   |          |          |

| <b>Double Display Fix input PID Controller</b> |                           |            |  |                 |                 |
|--|---------------------------|------------|--|-----------------|-----------------|
| <b>Model</b>                                   | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| TC-221P  | 72 X 72 X 60              | 1760       | Input : J Type<br>Output : 1 relay  SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC   | 90328910        | 18%             |
| TC-44  | 48 X 48 X 70              | 1760       | Input : Pt-100<br>Output : 1 relay  SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC   |                 |                 |
| TC-421P  | 48 X 48 X 70              | 1760       | Input : J/K (Configurable)<br>Output : 1 relay  SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC   |                 |                 |
| TC-442   | 48 X 48 X 70              | 2145       | Input : J /K (Configurable)<br>Output 1 : 1 relay  SSR,<br>Output 2 : Relay/SSR(factory set)<br>Control action : PID/TP/On-off (Configurable),<br>Supply : 100-270V AC |                 |                 |
| TC-443   | 48 X 48 X 70              | 2530       | Input : J /K (Configurable)<br>Output : 3 Relay & SSR Parallel to 1st relay<br>Control action : PID/TP/On-off (Configurable)<br>Supply : 100-270V AC                   |                 |                 |
| <b>20A Relay Possible in TC-421P</b>           |                           | <b>450</b> |  |                 |                 |

### Double Display Universal input PID Controller single relay (4+4 Digit)

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| UTC-121G | 96 X 96 X 50       | 2255 | Input : J/K/Pt-100(Configurable),<br>Output : 1 relay  SSR,<br>Control action : PID/On-off (Configurable)<br>Supply : 100-270V AC | 90328910 | 18%      |
| UTC-221G | 72 X 72 X 60       | 2255 |   |          |          |
| UTC-421G | 48 X 48 X 70       | 2255 |   |          |          |
| UTC-321P | 96 X 48X 95        | 2585 |   |          |          |

### Double Display Universal input PID Controller Double relay

| Model     | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-----------|--------------------|------|--|----------|----------|
| UTC-1202G | 96 X 96 X 50       | 2695 | Input : J/K/Pt-100(Configurable),<br>Output 1 : 1 relay  SSR,<br>Output 2 : Relay/SSR(factory set)<br>Control action : PID/TP/On-off (Configurable),<br>Supply : 100-270V AC | 90328910 | 18%      |
| UTC-2202G | 72 X 72 X 60       | 2695 |  |          |          |
| UTC-4202G | 48 X 48 X 95       | 2695 |  |          |          |
| UTC-3202  | 96 X 48X 95        | 2955 |  |          |          |

### Double Display Universal input PID Controller Three relay

| Model    | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| UTC-4203 | 48 X 48 X 95       | 2805 | Input : J/K/Pt-100(Configurable),<br>Output : 3 Relay<br>Control action : PID/TP/On-off (Configurable)<br>Supply : 100-270V AC | 90328910 | 18%      |
| UTC-3203 | 96 X 48 X 95       | 3355 |  |          |          |

| Universal input PID Controller With Analog Output & Modbus facility |                    |      |   |          |          |
|---|--------------------|------|---|----------|----------|
| Model   | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
| PTC-L12/PTC-1202  | 96 X 96 X 50       | 3975 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay ,<br>With 24V DC transmitter supply,<br>Supply : 100-270V AC   | 90328910 | 18%      |
| PTC-L12A/PTC-1202A  | 96 X 96 X 50       | 4500 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay + 4-20mA/0-10V DC (Factory set),<br>With 24V DC transmitter supply<br>Supply : 100-270V AC                 |          |          |
| PTC-L12-M1/<br>PTC-1202-M1  | 96 X 96 X 50       | 4865 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay+ Rs-485 Modbus ,<br>With 24V DC transmitter supply<br>Supply : 100-270V AC                                 |          |          |
| PTC-L12A-M1/<br>PTC-1202A-M1  | 96 X 96 X 50       | 5525 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay + 4-20mA/0-10V DC (Factory set)<br>+ RS-485 Modbus, With 24V DC transmitter supply<br>Supply : 100-270V AC |          |          |



|              |              |      |  |          |     |
|--------------|--------------|------|--|----------|-----|
| PTC-4202     | 48 X 48 X 95 | 3360 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay ,<br>With 24V DC transmitter supply<br>Supply : 100-270V AC   | 90328910 | 18% |
| PTC-4202A    | 48 X 48 X 95 | 3500 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay + 4-20mA/0-10V DC (Factory set),<br>With 24V DC transmitter supply<br>Supply : 100-270V AC                  |          |     |
| PTC-4202-M1  | 48 X 48 X 95 | 4375 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay+ Rs-485 Modbus ,<br>With 24V DC transmitter supply<br>Supply : 100-270V AC                                  |          |     |
| PTC-4202A-M1 | 48 X 48 X 95 | 4500 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 2 Relay + 4-20mA/0-10V DC (Factory set)<br>+ RS-485 Modbus, With 24V DC transmitter supply<br>Supply : 100 -270V AC |          |     |
| PTC-4201-M1  | 48 X 48 X 95 | 3730 | Input : J/K/PT-100/4-20mA/0-20mA/0-10V DC,<br>Output : 1 Relay+ Rs-485 Modbus ,<br>With 24V DC transmitter supply<br>Supply : 100-270V AC                                  |          |     |
| UTC-4201A    | 48 X 48 X 95 | 2385 | Input : J/K/PT-100<br>Output : 1 Relay + 4-20mA/0-10V DC (Factory set),<br>Supply : 100-270V AC  |          |     |

## PID Controller With Ampere Indication

| Model  | Size (H X W X D)mm | MRP         | Item Description   | HSN Code | GST Rate |
|--|--------------------|-------------|--|----------|----------|
| PID-2302-1C                                  | 72X 72 X 60        | 2750        | Input : J/K(Configurable),<br>Output : 2 Relay<br>Control action : PID/TP/On-off (Cofigurable), With<br>30A/60A Single CT<br>Supply : 100-270V AC        | 90328910 | 18%      |
| PID-2303-1C                                  | 72X 72 X 60        | 3050        | Input : J/K(Configurable),<br>Output : 3 Relay<br>Control action : PID/TP/On-off (Cofigurable), With<br>30A/60A Single CT<br>Supply : 100-270V AC        |          |          |
| PID-2303-3C                                  | 72X 72 X 60        | 3750        | Input : J/K(Configurable),<br>Output : 3 Relay<br>Control action : PID/TP/On-off (Configurable), With<br>30A/60A Three CT<br>Supply : 100 -270V AC       |          |          |
| PID-4201-1C                                  | 48 X 48 X 95       | 2860        | Input : J/K/Pt-100(Configurable),<br>Output : 1 Relay<br>Control action : PID/TP/On-off (Cofigurable), With<br>30A/60A Single CT<br>Supply : 100-270V AC |          |          |
| PID-4203-1C                                  | 48 X 48 X 95       | 3450        | Input : J/K/Pt-100(Configurable),<br>Output : 3 Relay<br>Control action : PID/TP/On-off (Cofigurable), With<br>30A/60A Single CT<br>Supply : 100-270V AC |          |          |
| <b>Optional RS-485 In PID-2303 Available</b> |                    | <b>1050</b> |  |          |          |

| <b>Profile Controller</b>                         |                           |             |   |                 |                 |
|---|---------------------------|-------------|---|-----------------|-----------------|
| <b>Model</b>                                      | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| PRC-1202  | 96 X 96 X 50              | 6050        | Input : J/K/Pt-100(Factory set) ,<br>Output : 1 relay for Heating With Ramp & Soak time setting upto 9 stage + 1 relay for End Alarm,<br>Control Action : On-Off<br>Supply : 100-250 V AC | 90328910        | 18%             |
| <b>Humidity Sensor</b>                            |                           |             |   |                 |                 |
| <b>Model</b>                                      | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| RH-100  |                           | 2600        | Range : Upto 100% RH With 2 Meter Cable   | 90329000        | 18%             |
| RH-85   |                           | 1550        | Range : Upto 85% RH,With 2 Meter Cable  |                 |                 |
| <b>Humidity Indicator With Alarm output</b>       |                           |             |   |                 |                 |
| <b>Model</b>                                      | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| MHT-1202  | 96 X 96 X 50              | 5500        | Input: Pt-100 + Humidity sensor<br>Output : 1R For temperature + 1R For Humidity<br>Supply : 100-250V AC  | 90328910        | 18%             |
| MHC-1101  | 96 X 96 X 50              | 4150        | Input: Humidity sensor<br>Output : 1Relay<br>Supply : 100-250V AC   |                 |                 |
| <b>RS-485 Modbus Output Available in MHT-1202</b> |                           | <b>1050</b> |   |                 |                 |

## Dual input Process Indicator

| Model                                      | Size (H X W X D)mm | MRP         | Item Description  | HSN Code | GST Rate |
|--|--------------------|-------------|---|----------|----------|
| DPI-122                                    | 96 X 96 X 50       | 3110        | Input 1: 4-20mA DC/0-20mA DC/0-10V DC /Pt-100(Factory set),<br>Input 2: 4-20mA DC/0-20mA DC/0-10V DC /Pt-100(Factory set) ,<br>Supply : 100-250V AC | 90303390 | 18%      |
| <b>Options : 1 Relay Output</b>            |                    | <b>725</b>  |   |          |          |
| <b>24V DC Transmitter supply @30mA</b>     |                    | <b>725</b>  |   |          |          |
| DPI-1824                                   | 96 X 96 X 50       | 5225        | Dual Input : 4-20mA DC/0-20mA DC/0-10V DC /J/K /Pt-100(Selectable),<br>Output : 2 Relay +24V DC Transmitter supply<br>Supply : 100-270V AC          | 90303390 | 18%      |
| <b>Options : Additional 2 Relay Output</b> |                    | <b>1450</b> |   |          |          |
| <b>Dual Retransmission Output</b>          |                    | <b>1700</b> |   |          |          |

## Process Control Instruments

### Process Indicator

| Model | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-------|--------------------|------|--|----------|----------|
| PI-11 | 96 x 96 x 42       | 1430 | Range : -999 to 9999,<br>Input : 4-20mA/0-20mA/0-10V DC (Selectable),<br>Supply : 100 -270V AC | 90303390 | 18%      |
| PI-21 | 72 x 72 x 42       | 1430 |  |          |          |
| PI-38 | 48 x 96 x 26       | 1650 |  |          |          |
| PI-41 | 48 x 48 x 46       | 1430 |  |          |          |
| PI-54 | 38 x 62 x 80       | 2915 |  |          |          |

### Process Indicator with Alarm Output

| Model  | Size (H X W X D)mm | MRP        | Item Description   | HSN Code | GST Rate |
|--|--------------------|------------|--|----------|----------|
| PIC-1101   | 96 x 96 x 50       | 2640       | Range : -999 to 9999,<br>Input : 4-20mA/0-20mA/0-10V DC (Selectable),<br>Output : 1 Relay + 24V DC Transmitter supply<br>Supply : 100 -270V AC | 90303390 | 18%      |
| PIC-38   | 48 x 96 x 58       | 2640       |  |          |          |
| <b>Options : Additional 1 Relay (PIC-1102)</b>     |                    | <b>725</b> |  |          |          |
| <b>Retransmission output available in PIC-1101</b> |                    | <b>850</b> |  |          |          |
| PIC-4202   | 48 x 48 x 95       | 3850       | Range : -999 to 9999,<br>Input : 4-20mA/0-20mA/0-10V DC (Selectable),<br>Output : 2 Relay + 24V DC Transmitter supply<br>Supply : 100 -270V AC |          |          |

### Loop Powered Transmitter

| Model  | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|--------|--------------------|------|---|----------|----------|
| LPT-45 | Diameter : 45mm    | 1650 | Input : J/K/Pt-100 (Factory set),<br>Output : 4-20mA, Head Mounting<br>Supply : 24V DC Loop Powered | 90303390 | 18%      |
| LPT-63 | 76 x 27 x 116      | 2075 | Input : J/KPt-100 (factory set)<br>Output : 4-20mA, Din rail<br>Supply : 24V DC Loop Powered        |          |          |

| <b>Synchronizer Unit</b>  |                           |             |  |                 |                 |
|---|---------------------------|-------------|--|-----------------|-----------------|
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| SN-126 -4   | 75 x 45 x 110             | 3720        | Input : 3 Wire 10K Pot,<br>Output : 0 to 10V DC (Up to 6 Channel),<br>Supply : 230V AC         | 90303390        | 18%             |
| SN-126-5  | 75 x 45 x 110             | 4435        |  |                 |                 |
| SN-126 -6   | 75 x 45 x 110             | 5720        |  |                 |                 |
| <b>Load Cell Indicator With Relay output</b>                      |                           |             |  |                 |                 |
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| LD-1006   | 96 x 96 x 52              | 4070        | Input : 2mV/V,<br>Excitation Voltage : 10V DC ,<br>Output : 1 Relay,<br>Supply : 230V AC       | 90303390        | 18%             |
| <b>Options : Additional 1 Relay</b>                               |                           | <b>725</b>  |  |                 |                 |
| <b>Retransmission Output</b>                                      |                           | <b>850</b>  |  |                 |                 |
| <b>RS-485 Modbus</b>  |                           | <b>1050</b> |  |                 |                 |
| <b>Multi Mode Process Indicator</b>                               |                           |             |  |                 |                 |
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| SPI-421 (1 Mode)  | 48 X 48 X 70              | 5335        | Range : -999 to 9999,<br>Input : 4-20mA/0-20mA/0-10V DC (Selectable),<br>Supply : 100 -270V AC | 90303390        | 18%             |
| SPI-424 ( 4 Mode)   | 48 X 48 X 70              | 5775        |  |                 |                 |
| SPI-427 (7 Mode)  | 48 X 48 X 70              | 6410        |  |                 |                 |
| <b>Note : Auxiliary supply 24V DC Available in selected model</b> |                           | <b>450</b>  |  |                 |                 |

| <b>Signal Isolator</b> |                           |            |  |                 |                 |
|------------------------|---------------------------|------------|--|-----------------|-----------------|
| <b>Model</b>           | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| MI-431                 | 100 x 12.5 x 115          | 3050       | Input : 4-20mA/0-20mA/0-10V DC (Factory set)<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel), with Transmitter Supply 24V DC<br>Supply : 100-250V AC OR 24V DC | 90303390        | 18%             |
| MI-532                 | 100 x 17.5 x 115          | 3650       | Input : 4-20mA/0-20mA/0-10V DC (Factory set)<br>Output : 4-20mA/0-20mA/0-10V DC (Dual Channel), with Transmitter Supply 24V DC<br>Supply : 100-250V AC OR 24V DC   |                 |                 |
| MI-532P                | 100 x 17.5 x 115          | 4175       | Input : Pt-100, Range : Factory Set<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC  |                 |                 |
| MI-631                 | 76 x 27 x 85              | 2075       | Input : 4-20mA/0-20mA/0-10V DC (Factory set)<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC                                 |                 |                 |
| MI-632                 | 76 x 27 x 85              | 2360       | Input : 4-20mA/0-20mA/0-10V DC (Factory set)<br>Output : 4-20mA/0-20mA/0-10V DC (Dual Channel)<br>Supply : 100-250V AC OR 24V DC                                   |                 |                 |
| MI-631P                | 76 x 27 x 85              | 2650       | Input : Pt-100, Range : Factory Set<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC  |                 |                 |
| MI-631T                | 76 x 27 x 85              | 2475       | Input : J/k (Factory set), Range : Factory Set<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC                               |                 |                 |
| MI-632T                | 76 x 27 x 85              | 2850       | Input : J/k (Factory set), Range : Factory Set<br>Output : 4-20mA/0-20mA/0-10V DC (Dual Channel)<br>Supply : 100-250V AC OR 24V DC                                 |                 |                 |

## Current Transducer & Voltage Transducer

| Model   | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|---------|--------------------|------|--|----------|----------|
| CTR-63  | 76 x 27 x 116      | 2640 | Input : 0-5A AC<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC        | 90303390 | 18%      |
| CTR-632 | 76 x 27 x 116      | 3015 | Input : 0-5A AC<br>Output : 4-20mA/0-20mA/0-10V DC (Dual Channel)<br>Supply : 100-250V AC OR 24V DC          | 90303390 | 18%      |
| VTR-63  | 76 x 27 x 116      | 2950 | Input : AC /DC Voltage<br>Output : 4-20mA/0-20mA/0-10V DC (Single Channel)<br>Supply : 100-250V AC OR 24V DC | 90303390 | 18%      |
| VTR-632 | 76 x 27 x 116      | 3250 | Input : AC /DC Voltage<br>Output : 4-20mA/0-20mA/0-10V DC (Dual Channel)<br>Supply : 100-250V AC OR 24V DC   | 90303390 | 18%      |

## Flow Totaliser

| Model                               | Size (H X W X D)mm | MRP         | Item Description  | HSN Code | GST Rate |
|-------------------------------------|--------------------|-------------|---|----------|----------|
| MFC-1048                            | 96 x 96 x 52       | 5775        | Range : 8D Total flow , 4D Flow rate<br>Input : 4-20mA,<br>Output : 1 relay+24V DC Transmitter supply,<br>Supply : 100 -250V AC | 90303390 | 18%      |
| <b>Options : Additional 1 Relay</b> |                    | <b>725</b>  |   |          |          |
| <b>Retransmission Output</b>        |                    | <b>850</b>  |   |          |          |
| <b>RS-485 Modbus</b>                |                    | <b>1050</b> |   |          |          |
| MFC-1048P                           | 96 x 96 x 52       | 5775        | Range : 8D Total flow , 4D Flow rate<br>Input : Pulse<br>Output : 1 relay+24V DC Transmitter supply,<br>Supply : 100 -250V AC   | 90303390 | 18%      |
| <b>Retransmission Output</b>        |                    | <b>850</b>  |   |          |          |
| <b>RS-485 Modbus</b>                |                    | <b>1050</b> |   |          |          |
| MFC-3016D/MFC-3016A                 | 48 x 96 x 60       | 6050        | Range : 8D Total flow , 4D Flow rate<br>Input : Pulse/4-20mA<br>Supply : 100 -250V AC   |          |          |
| <b>Options: RS-485 Modbus</b>       |                    | <b>1050</b> |   |          |          |
| <b>Retransmission Output</b>        |                    | <b>850</b>  |   |          |          |



| Process Scanner & Data Logger |                    |       |   |          |          |
|-------------------------------|--------------------|-------|---|----------|----------|
| Model                         | Size (H X W X D)mm | MRP   | Item Description  | HSN Code | GST Rate |
| MS-1208                       | 96 x 96 x 52       | 4700  | Input : J/K/Pt-100 (Selectable)<br>Supply : 100-270V AC   | 90303390 | 18%      |
| MS-1208A                      | 96 x 96 x 52       | 4700  | Input : 4-20mA/0-20mA/0-10V DC(Selectable)<br>Supply : 100-270V AC                                      |          |          |
| MS-1208-M1                    | 96 x 96 x 52       | 6040  | Input : J/K/Pt-100 (Selectable),<br>Output : RS-485 Modbus<br>Supply : 100-270V AC                      |          |          |
| MS-1208A-M1                   | 96 x 96 x 52       | 6040  | Input : 4-20mA/0-20mA/0-10V DC(Selectable),<br>Output : RS-485 Modbus<br>Supply : 100-270V AC           |          |          |
| MS-1248                       | 96 x 96 x 52       | 11105 | Input : J/K/Pt-100 (Selectable)<br>Output : 4 Relay<br>Supply : 100-270V AC                             |          |          |
| MS-1248-M1                    | 96 x 96 x 52       | 12735 | Input : J/K/Pt-100 (Selectable)<br>Output : 4 Relay + RS-485 Modbus<br>Supply : 100-270V AC             |          |          |
| MS-1248A                      | 96 x 96 x 52       | 11105 | Input : 4-20mA/0-20mA/0-10V DC (Selectable)<br>Output : 4 Relay<br>Supply : 100-270V AC                 |          |          |
| MS-1248A-M1                   | 96 x 96 x 52       | 12735 | Input : 4-20mA/0-20mA/0-10V DC (Selectable)<br>Output : 4 Relay + RS-485 Modbus<br>Supply : 100-270V AC |          |          |
| MS-1248U                      | 96 x 96 x 52       | 16435 | Input : J/K/Pt-100 (Selectable)<br>Output : 4 Relay + USB Port<br>Supply : 100-270V AC                  |          |          |
| MSU-1248                      | 96 x 96 x 52       | 17225 | Input : J/K/Pt-100/4-20mA/0-10V DC/0-20mA<br>(Selectable)<br>Output : 4 Relay<br>Supply : 100-270V AC   |          |          |

|  |                |             |   |          |     |
|--|----------------|-------------|---|----------|-----|
| MSU-1248-M1  | 96 x 96 x 52   | 18745       | Input : J/K/Pt-100/4-20mA/0-10V DC/0-20mA<br>(Selectable)<br>Output : 4 Relay +Modbus<br>Supply : 100-270V AC         | 90303390 | 18% |
| MSU-1248U  | 96 x 96 x 52   | 22420       | Input : J/K/Pt-100/4-20mA/0-10V DC/0-20mA<br>(Selectable)<br>Output : 4 Relay +USB Port<br>Supply : 100-270V AC       |          |     |
| MS-5716  | 192 x 96 x 130 | 16275       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Supply : 100-270V AC                                     |          |     |
| MS-5716R   | 192 x 96 x 130 | 21790       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Output : 8 relay<br>Supply : 100-270V AC                 |          |     |
| MS-5716-M1   | 192 x 96 x 130 | 19245       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Output : RS-485Modbus<br>Supply : 100-270V AC            |          |     |
| MS-5716U   | 192 x 96 x 130 | 21790       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Output : USB Port<br>Supply : 100-270V AC                |          |     |
| MS-5716RU  | 192 x 96 x 130 | 25990       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Output : 8 relay+ USB Port<br>Supply : 100-270V AC       |          |     |
| MS-5716R-M1  | 192 x 96 x 130 | 25990       | Input : J/K/Pt-100/4-20mA/0-20mA/0-10V DC<br>(Selectable)<br>Output : 8 relay + RS-485 Modbus<br>Supply : 100-270V AC |          |     |
| <b>Note : Aux Supply 24V DC available in All Scanner model</b> |                | <b>1300</b> |   |          |     |

## Jumbo Displays

### Jumbo Display Temperature indicator

| Model                              | Size (H X W X D)mm | MRP        | Item Description  | HSN Code | GST Rate |
|------------------------------------|--------------------|------------|---|----------|----------|
| UTI-3004 (Single Side)             | 130 X 235 X 50     | 6215       | Input : J/K/Pt-100 (Selectable),<br>Display : 2.25 Inch,4 Digit<br>Supply : 100-270V AC | 90303390 | 18%      |
| UTI-3004 (Dual Side)               | 130 X 235 X 50     | 7700       |   |          |          |
| UTI-6004 (Single Side)             | 160 X 380 X 50     | 7500       | Input : J/K/Pt-100 (Selectable),<br>Display : 4 Inch,4 Digit<br>Supply : 100-270V AC    | 90303390 | 18%      |
| UTI-6004 (Dual Side)               | 160 X 380 X 50     | 11525      |   |          |          |
| <b>Option : Additional 1 Relay</b> |                    | <b>725</b> |   |          |          |

### Jumbo Display Programmable timer

| Model                  | Size (H X W X D)mm | MRP   | Item Description  | HSN Code | GST Rate |
|------------------------|--------------------|-------|---|----------|----------|
| UTR-6004 (Single Side) | 160 X 380 X 50     | 9250  | Range : 0-9999 Sec/Min/Hour Selectable,<br>OnDelay/Off Delay/Cyclic Timer<br>Output : 1R2C/O,<br>Supply : 100-270V AC | 90303390 | 18%      |
| UTR-6004 (Dual Side)   | 160 X 380 X 50     | 13545 |   |          |          |

### Jumbo Display Process Indicator indicator

| Model                              | Size (H X W X D)mm | MRP        | Item Description   | HSN Code | GST Rate |
|------------------------------------|--------------------|------------|--|----------|----------|
| PIC-3004A (Single Side)            | 130 X 235 X 50     | 7150       | Input : 4-20mA/0-10VDC/0-20mA(Selectable)<br>Display : 2.25 Inch,4 Digit<br>Supply : 100-270V AC   | 90303390 | 18%      |
| PIC-3004A (Dual Side)              | 130 X 235 X 50     | 8965       |  |          |          |
| PIC-6004A (Single Side)            | 160 X 380 X 50     | 9785       | Input : 4-20mA/0-10VDC/0-20mA(Selectable)<br>Display : 4 Inch,4 Digit<br>Supply : 100-270V AC  |          |          |
| PIC-6004A (Dual Side)              | 160 X 380 X 50     | 13250      |  |          |          |
| PTC-8004A(Single Side)             | 330 x 823 x 50     | 33000      | Input : 4-20mA/0-10VDC/0-20mA/J/K/PT-100(Selectable),With 24V DC Transmitter supply<br><b>Display : 8 Inch,4 Digit</b><br>Supply : 100-270V AC |          |          |
| PTC-6004A(Single Side)             | 160 X 380 X 50     | 11740      | Input : 4-20mA/0-10VDC/0-20mA/J/K/PT-100(Selectable),<br>Display : 4 Inch,4 Digit<br>Supply : 100-270V AC                                      |          |          |
| PTC-6004A (Dual Side )             | 160 X 380 X 50     | 14885      |  |          |          |
| <b>Options: Additional 1 relay</b> |                    | <b>725</b> |  |          |          |
| <b>Transmitter supply 24V DC</b>   |                    | <b>725</b> |  |          |          |

### Jumbo Display MPM Indicator - Encoder Input

| Model                  | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|------------------------|--------------------|-------|--|----------|----------|
| MSI-3004 (Single Side) | 130 X 235 X 50     | 8595  | Input : NPN/PNP Encoder<br>Display : 2.25 Inch,4 Digit<br>Parameter : MPM /COUNT/RPM<br>Supply : 100-270V AC | 90291090 | 18%      |
| MSI-3004 (Dual Side)   | 130 X 235 X 50     | 10495 |  |          |          |
| MSI-6004 (Single Side) | 160 X 380 X 50     | 11850 | Input : NPN/PNP Encoder<br>Display : 4 Inch,4 Digit<br>Parameter : MPM /COUNT/RPM<br>Supply : 100-270V AC    |          |          |
| MSI-6004 (Dual Side)   | 160 X 380 X 50     | 14950 |  |          |          |

### Jumbo Display Programmable Length Counter

| Model                         | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|-------------------------------|--------------------|-------|--|----------|----------|
| LC-9004                       | 160 X 375 X 50     | 22875 | Range : 6 Digit Total length, 4 Digit MPM<br>Input Proximity (NPN/PNP), Diameter Selectable<br>Output : 1R On Total length, Double Display<br>(2.25 Inch Each)<br>Supply : 100-250V AC | 90291090 | 18%      |
| Option : RS-485 Modbus Output |                    | 2000  |  |          |          |

### Jumbo Display Programmable Counter

| Model                       | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|-----------------------------|--------------------|-------|--|----------|----------|
| PC-3004 (Single Side)       | 130 X 235 X 50     | 7475  | Input : NPN/PNP Proximity/Microswitch(Selectable),<br>Display : 2.25 Inch,4 Digit<br>Parameter : Counter<br>Supply : 100-270V AC | 90291090 | 18%      |
| PC-3004 (Dual Side)         | 130 X 235 X 50     | 9375  |  |          |          |
| PC-6004 (Single Side)       | 160 X 380 X 50     | 12750 | Input : NPN/PNP Proximity/Microswitch(Selectable),<br>Display : 4 Inch,4 Digit<br>Parameter : Counter<br>Supply : 100-270V AC    | 90291090 | 18%      |
| PC-6004 (Dual Side)         | 160 X 380 X 50     | 15150 |  |          |          |
| PC-6006 (Single Side)       | 165 X 570 X 50     | 18750 | Input : NPN/PNP Proximity/Microswitch(Selectable),<br>Display : 4 Inch,6 Digit<br>Parameter : Counter<br>Supply : 100-270V AC    |          |          |
| Options: Additional 1 relay |                    | 725   |  |          |          |

### Jumbo Display Humidity + Temperature Controller

| Model    | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|----------|--------------------|-------|--|----------|----------|
| MHT-9044 | 160 X 375 X 50     | 24500 | Input: Pt-100+ RH sensor<br>Output : 1R For temperature + 1R For Humidity<br>Double Display (2.25 Inch Each)<br>Supply : 100-250V AC | 90328910 | 18%      |

| <b>Jumbo Display MPM &amp; RPM Indicator</b> |                           |             |  |                 |                 |
|--|---------------------------|-------------|--|-----------------|-----------------|
| <b>Model</b>                                 | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| MPM-3004/RPM-3004<br>(Single Side)           | 130 X 235 X 50            | 8750        | Input : NPN/PNP Proximity/Microswitch(Selectable),<br>Display : 2.25 Inch,4 Digit<br>Parameter : MPM/RPM<br>Supply : 100-270V AC | 90291090        | 18%             |
| MPM-3004/RPM-3004<br>(Dual Side)             | 130 X 235 X 50            | 10350       |  |                 |                 |
| MPM-6004/RPM-6004<br>(Single Side)           | 160 X 380 X 50            | 10150       |  |                 |                 |
| MPM-6004/RPM-6004<br>(Dual Side)             | 160 X 380 X 50            | 13750       |  |                 |                 |
| <b>Jumbo Display Indicator -MODBUS INPUT</b> |                           |             |  |                 |                 |
| <b>Model</b>                                 | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| RS-8004 (Single Side)                        | 330 x 823 x 50            | 34500       | Input : RS-485 MODBUS<br>Display : 8 Inch,4 Digit<br>Supply : 100-270V AC  | 90291090        | 18%             |
| RS-6004 (Single Side)                        | 160 X 380 X 50            | 12750       |  |                 |                 |
| RS-6004 (Dual Side)                          | 160 X 380 X 50            | 15150       |  |                 |                 |
| RS-6006 (Single Side)                        | 165 X 570 X 50            | 17250       |  |                 |                 |
| <b>Note : 24V DC Aux.Supply Available</b>    |                           | <b>1050</b> |  |                 |                 |

## Programmable Timers

### Time Totaliser / Hour Meter

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| DTT-1000 | 96 X 96 X 50       | 1360 | 6 Digit Display,<br>Range : 0-9999.59 Hour/Min/Sec<br>Input : 230V AC enable pulse with Power Fail<br>Memory,<br>Supply : 230V AC | 85369090 | 18%      |
| DTT-2000 | 72 X 72 X 60       | 1360 |   |          |          |
| DTT-3000 | 48 X 96 X 55       | 1360 |   |          |          |
| DTT-56G  | 36 X 62 X 75       | 1360 |   |          |          |
| DTT-5000 | 36 X 72 X 95       | 1360 |   |          |          |

### Thumbwheel 3 Digit Timer

| Model      | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|------------|--------------------|------|---|----------|----------|
| MDT-3300   | 96 X 48 X 85       | 2040 | Range:0-.99/9.9/99/9.99/99.9/999 Sec/Min (factory set),<br>Output : 1R2C/O,<br>Supply : 230V AC | 85369090 | 18%      |
| MDT-1300ST | 96 X 96 X 50       | 2040 |   |          |          |
| MDT-2300ST | 72 X 72 X 60       | 2040 |   |          |          |

### Thumbwheel 3 Digit Timer

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| MDT-1310 | 96 X 96 X 50       | 1815 | Range : 99.9/999 Sec/Min Selectable ,<br>On delay Timer<br>Output : 1R2C/O,<br>Supply : 230V AC | 85369090 | 18%      |
| MDT-2312 | 72 X 72 X 60       | 1815 |   |          |          |

### Thumbwheel 3 Digit Timer

| Model     | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-----------|--------------------|------|---|----------|----------|
| MDT-1310F | 96 X 96 X 50       | 1935 | Range : 9.99/99.9/999 Sec/Min/Hour Selectable ,<br>On delay Timer/Off delay timer<br>Output : 1R2C/O,<br>Supply : 230V AC | 85369090 | 18%      |
| MDT-2312F | 72 X 72 X 60       | 1935 |   |          |          |
| MDT-4310  | 48 X 48 X 100      | 1715 |   |          |          |

## Din rail Display timer

| Model                             | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-----------------------------------|--------------------|------|---|----------|----------|
| DIN -63                           | 76 X 28 X 85       | 1540 | Range : 9.99/99.9/999 Sec/Min/Hour Selectable ,<br>On delay Timer/Off delay timer<br>Output : 1R2C/O,<br>Supply : 100-250V AC | 85369090 | 18%      |
| DIN -63C                          |                    | 1540 | Range : 9.99/99.9/999 Sec/Min/Hour (Selectable)<br>Cyclic Timer<br>Output : 1R2C/O,<br>Supply : 100-250V AC                   |          |          |
| Model                             | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
| DI-22<br>On-Off Delay timer       | 90 X 22.5 X 67.5   | 935  | Range : 0.1 Second to 10 Hours (Selectable)<br>Output : 1R1C/O<br>Supply : 230V AC & 24V DC                                   | 85369090 | 18%      |
| DI-22U<br>On-Off Delay timer      |                    | 1430 | Range : 0.1 Second to 10 Hours (Selectable)<br>Output : 1R2C/O<br>Supply : 12 to 240V DC & 20 to 240V AC                      |          |          |
| FRT-22<br>Forward - Reverse timer |                    | 1595 | Range : 0.1 Second to 10 Hours (Selectable)<br>Output : 2R1C/O<br>Supply : 230V AC  |          |          |
| CYL-22<br>Cyclic timer            |                    | 1265 | Range : 0.1 Second to 10 Hours (Selectable)<br>Output : 1R2C/O<br>Supply : 230V AC  |          |          |
| DT-10S/30s/60S                    |                    | 850  | Range : 10S/30S/60S<br>Output : 1R1C/O  |          |          |
| DT-10S-4/30s-4/60S-4              |                    | 1075 | Supply : 230V AC/415V AC  |          |          |
| SD-224                            |                    | 1265 | Range : 1 Sec To 60 Sec<br>Output : 2R1C/O  |          |          |
| SD-22<br>Star-Delta timer         |                    | 1045 | Supply : 415V AC/230V AC  |          |          |
| POD-22<br>Power Off Delay timer   |                    | 2250 | Range : 0 Sec To 180 Sec<br>Output : 1R2C/O<br>Supply : 100-270V AC   |          |          |



## Universal Range Digital Timers

| Model    | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| UTR-1033 | 96 X 96 X 50       | 1935 | Range : 0-9999 Sec/Min/Hour Selectable,<br>OnDelay/Off Delay/Cyclic Timer<br>Output : 1R2C/O,<br>Supply : 100-270V AC                    | 85369090 | 18%      |
| UTR-2033 | 72 X 72 X 45       | 1935 |  |          |          |
| UTR-433  | 48 X 48 X 70       | 1935 |  |          |          |
| UTR-1244 | 96 X 96 X 50       | 2650 |  |          |          |
| UTR-2244 | 72 X 72 X 45       | 2650 |  |          |          |
| UTR-4244 | 48 X 48 X 70       | 2650 |  |          |          |
| CTU-4244 | 48 X 48 X 70       | 3315 |  |          |          |
| UTR-413  | 48 X 48 X 70       | 1500 | Range : 0-999 Sec/Min/Hour Selectable,<br><b>Single Display</b> ,OnDelay/Off Delay/Cyclic Timer<br>Output : 1R2C/O,<br>Supply100-270V AC |          |          |

## Sequential timer

| Model    | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|----------|--------------------|------|--|----------|----------|
| SQT-1244 | 96 X 96 X 50       | 7975 | 12 Channel Sequential timer,<br>Output : 12 Relay,<br>Supply : 100-270V AC                     | 85369090 | 18%      |
| SQT-1044 |                    | 5280 | 8 Channel Sequential timer,<br>Output : 8 Relay, With Cascade Facility<br>Supply : 100-270V AC |          |          |
| SQT-1022 |                    | 2930 | 4 Channel Sequential timer,<br>Output : 4 Relay,<br>Supply : 100-270V AC                       |          |          |
| CMT-1022 |                    | 3250 | 4 Channel Combinational timer,<br>Output : 4 Relay,<br>Supply : 100-270V AC                    |          |          |
| CMT-1044 |                    | 5575 | 8 Channel Combinational timer,<br>Output : 8 Relay,<br>Supply : 100-270V AC                    |          |          |

**Programmable Counters**

**Count Totaliser**

| Model   | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|---------|--------------------|------|--|----------|----------|
| CT-1000 | 96 X 96 X 42       | 1360 | Range : 0 - 999999Count ,<br>Input : Proximity (NPN/PNP)/230V AC (Factory set)<br>Supply : 230V AC | 90291090 | 18%      |
| CT-2000 | 72 X 72 X 50       | 1360 |  |          |          |
| CT-3000 | 48 X 96 X 60       | 1360 |  |          |          |
| CT-5000 | 36 X 72 X 95       | 1360 |  |          |          |
| CT-56G  | 38 X 62 X 75       | 1360 |  |          |          |

**RPM Indicator**

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| RPM-1201 | 96 X 96 X 42       | 1500 | Range : 4-5000 RPM ,<br>Input : Proximity (NPN/PNP)<br>Supply : 230V AC | 90291090 | 18%      |
| RPM-2201 | 72 X 72 X 50       | 1500 |   |          |          |
| RPM-3201 | 48 X 96 X 60       | 1500 |   |          |          |
| RPM-4201 | 48 X 48 X 95       | 1500 |   |          |          |

**Thumbwheel counter**

| Model     | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-----------|--------------------|------|--|----------|----------|
| TWS-1400F | 96 X 96 X 50       | 3290 | Range : 0 -9999 Count ,<br>Input : Proximity (NPN/PNP),<br>Output : 1R2C/O,<br>Supply : 100-270V AC<br>With power fail memory facility | 90291090 | 18%      |
| TWS-2500F | 72 X 72 X 75       | 3290 |  |          |          |

**Thumbwheel counter**

| Model       | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-------------|--------------------|------|---|----------|----------|
| TWS-1400-5D | 96 X 96 X 100      | 3685 | Range : 5D/6D Count ,<br>Input : Proximity (NPN/PNP),<br>Output : 1R2C/O,<br>Supply : 100-270V AC | 90291090 | 18%      |
| TWS-2500-5D | 72 X 72X 100       | 3685 |   |          |          |
| TWS-1400-6D | 96 X 96 X 100      | 4125 |   |          |          |
| TWS-1400ST  | 96 X 96 X 50       | 2835 | Range : 0 -9999 Count ,<br>Input : Proximity PNP,<br>Output : 1R2C/O,<br>Supply : 100-270V AC     |          |          |
| TWS-2500ST  | 72 X 72X 100       | 2835 |   |          |          |

| <b>MPM Indicator</b>                            |                           |            |  |                 |                 |
|---|---------------------------|------------|--|-----------------|-----------------|
| <b>Model</b>                                    | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| MPM-1044  | 96 X 96 X 50              | 2950       | Range : 0 -9999 MPM,<br>Input : Proximity (NPN/PNP)<br>Supply : 100 -250V AC   | 90291090        | 18%             |
| MPM-2044  | 72 X 72 X 75              | 2950       |  |                 |                 |
| <b>MPM Ratio Indicator</b>                      |                           |            |  |                 |                 |
| <b>Model</b>                                    | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| MSI-2044  | 96 X 96 X 50              | 5950       | Range : 0 -9999 MPM,<br>Input : Dual NPN Proximity,<br>Upper Display Show Ratio,<br>display show Separate MPM<br>Supply : 100 -250V AC | 90291090        | 18%             |
|   |                           |            | Lower  |                 |                 |
| <b>RPM Indicator With Alarm Output</b>          |                           |            |  |                 |                 |
| <b>Model</b>                                    | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| RPM-1044  | 96 X 96 X 50              | 3575       | Range : 0 -9999 RPM ,<br>Input Proximity (NPN/PNP),<br>Output : 1R1C/O,<br>Supply : 100-270V AC  | 90291090        | 18%             |
| RPM-2044  | 72 X 72 X 75              | 3575       |  |                 |                 |
| <b>Options : Additional 1 relay</b>             |                           | <b>725</b> |  |                 |                 |
| <b>RPM Indicator With Retransmission output</b> |                           |            |  |                 |                 |
| RPM-1044RT                                      | 96 X 96 X 50              | 4575       | Range : 0 -9999 RPM ,<br>Input Proximity (NPN/PNP),<br>Output : 4-20mA/0-10V DC Retransmission<br>Supply : 100-270V AC                 | 90291090        | 18%             |

| Programmable Counter                                       |                    |            |   |          |          |
|--|--------------------|------------|---|----------|----------|
| Model  | Size (H X W X D)mm | MRP        | Item Description  | HSN Code | GST Rate |
| PC-1006D   | 96 X 96 X 42       | 2145       | Range : 0 -999999 Count,<br>Input Proximity (NPN/PNP),<br>Output : 1R1C/O,Single Display<br>Supply : 100-270V AC  | 90291090 | 18%      |
| PC-2006  | 72 X 72 X 85       | 2145       |   |          |          |
| PC-3006  | 48 X 96 X 120      | 2145       |   |          |          |
| PC-1044  | 96 X 96 X 42       | 2145       |   |          |          |
| PC-2044  | 72 X 72 X 85       | 2145       |   |          |          |
| PC-444   | 48 X 48 X 95       | 2145       |   |          |          |
| <b>Options : Additional 1 relay in PC-1044 ,PC-2044</b>    |                    | <b>725</b> |   |          |          |
| Programmable Length Counter                                |                    |            |   |          |          |
| Model  | Size (H X W X D)mm | MRP        | Item Description  | HSN Code | GST Rate |
| LC-1046D   | 96 X 96 X 42       | 2145       | Range : 6 Digit Total length, 4 Digit MPM<br>Input Proximity (NPN/PNP), Diameter Selectable<br>Output : 1R On total length ,Double display<br>Supply : 230V AC                          | 90291090 | 18%      |
| LC-2046  | 72 X 72 X 50       | 2145       |   |          |          |
| LC-445 (5 Digit )  | 48 X 48 X 95       | 2290       |   |          |          |
| LC-3006 (Single display 6 Digit)                           | 48 X 96 X 110      | 2145       |   |          |          |
| <b>Options : Additional 1 relay Available in LC-1046D,</b> |                    | <b>725</b> |   |          |          |
| <b>Encoder Input Available in LC-1046D, LC -2046</b>       |                    | <b>975</b> |   |          |          |
| LC-1048-M1   | 96 X 96 X 50       | 4585       | Range : 8 Digit Total length, 4 Digit MPM<br>Input Proximity (NPN/PNP), Diameter Selectable<br>Output : 1R On Total length, Double Display,<br>With RS-485 MODbus ,<br>Supply : 230V AC |          |          |

| <b>Programmable Batch Counter</b>                |                           |            |   |                 |                 |
|--|---------------------------|------------|---|-----------------|-----------------|
| <b>Model</b>                                     | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| BC-1046D   | 96 X 96 X 42              | 2145       | Range : 6 Digit Total Count , 4 Digit Batch Count<br>Input Proximity (NPN/PNP),<br>Output : 1R1C/O On Batch count ,<br>Double display<br>Supply : 230V AC | 90291090        | 18%             |
| BC-2046  | 72 X 72 X 50              | 2145       |   |                 |                 |
| BC-445 (5 Digit )                                | 48 X 48 X 95              | 2290       |   |                 |                 |
| <b>Options : Additional 1 relay Available in</b> |                           | <b>725</b> |   |                 |                 |
| <b>Tablet counter</b>                            |                           |            |   |                 |                 |
| <b>Model</b>                                     | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| TBC-1048   | 96 X 96 X 50              | 4950       | Range : 8 Digit Total Count , 4 Digit RPM<br>Input Proximity (NPN/PNP),<br>Output : 1R1C/O On total count ,Double display<br>Supply : 230V AC             | 90291090        | 18%             |
| <b>Programmable Counter + RPM</b>                |                           |            |   |                 |                 |
| <b>Model</b>                                     | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| MMC-1046RD                                       | 96 X 96 X 42              | 2350       | Range : 6 Digit Total Count , 4 Digit RPM<br>Input Proximity (NPN/PNP),<br>Output : 1R1C/O On Total count ,<br>Double display<br>Supply : 230V AC         | 90291090        | 18%             |
| MMC-2046R  | 72 X 72 X 50              | 2350       |   |                 |                 |

**Clutch Brake controller**

| Model     | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-----------|--------------------|------|---|----------|----------|
| MMC-1046T | 96 X 96 X 50       | 4950 | Input : CMS + NPN Proximity,<br>Output : 1 Relay To operate Clutch & Brake,<br>Supply : 100 -250V AC                              | 90291090 | 18%      |
| MC-1003   | 96 X 96 X 50       | 8280 | Input : CMS + NPN Proximity,<br>Output : 1 Relay To operate Clutch & Brake, 1<br>Relay for Batch counter<br>Supply : 100 -250V AC | 90291090 | 18%      |

**Vibrator Controller**

| Model    | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|----------|--------------------|------|---|----------|----------|
| MVC-72N  | 72 X 72 X 50       | 2195 | Input : NPN/PNP Proximity,<br>Range : 1 to 99% ,<br>Output : 0 to 110V AC Corresponding to percentage<br>input ,5A Load capacity<br>Supply : 230V AC  | 90291090 | 18%      |
| MVC-7210 | 72 X 72 X 85       | 3150 | Input : NPN/PNP Proximity,<br>Range : 1 to 99% ,<br>Output : 0 to 110V AC Corresponding to percentage<br>input ,10A Load capacity<br>Supply : 230V AC | 90291090 | 18%      |

**Sequential counter**

| Model    | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|----------|--------------------|-------|--|----------|----------|
| MPC-2412 | 72 X 144 x 120     | 17050 | Range : 0 to 9999 Count,<br>Input : NPN Proximity,<br>Output : 3 Relay<br>Supply : 230V AC | 90291090 | 18%      |

## Photo Electric contoller

| Model     | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-----------|--------------------|------|--|----------|----------|
| MPC-1061L | 96 X 96 X 50       | 4485 | Input : CMS + NPN Proximity ,<br>Output: Forward & Reverse Windind @2A,110V AC & Buzzer output for batch count<br>Supply : 110V AC | 90291090 | 18%      |
| MPC-1062L | 96 X 96 X 50       | 4485 | Input : CMS + NPN Proximity,<br>Output: Forward & Reverse Winding @2A,230V AC & Buzzer output for batch count<br>Supply : 230V AC  |          |          |
| MPC-5062  | 192 X 96 X 130     | 5010 | Input : CMS + NPN Proximity,<br>Output: Forward & Reverse Winding @2A,110V AC<br>Supply : 110V AC                                  |          |          |
| MPC-5062  | 192 X 96 X 130     | 5010 | Input : CMS + NPN Proximity,<br>Output: Forward & Reverse Windind @2A,230VAC<br>Supply : 230V AC                                   |          |          |

## FFS Control Unit

| Model                             | Size (H X W X D)mm | MRP   | Item Description  | HSN Code | GST Rate |
|-----------------------------------|--------------------|-------|---|----------|----------|
| MPC-5265                          | 192 X 96 X 130     | 13830 | Input : CMS +1 or 2 NPN Proximity , Batch cutter proximity<br>Output For Clutch & Break @2A , 24V DC +7 Relay<br>Supply : 230V AC | 90291090 | 18%      |
| PFLC-68<br>(Touch Screen Display) | 96 X 96 X 52       | 17855 | Input : CMS +1 or 2 NPN Proximity , Batch cutter proximity<br>Output For Clutch & Break @2A , 24V DC +8 Relay<br>Supply : 24V DC  |          |          |
| MPC-1065<br>(LCD Display)         | 96 X 96 X 50       | 11760 | Input : CMS +1 or 2 NPN Proximity , Batch cutter proximity<br>Output For Clutch & Break @2A , 24V DC +4 Relay<br>Supply : 24V DC  | 90291090 | 18%      |

| <b>Color Mark Sensor</b>                         |                           |            |  |                 |                 |
|--|---------------------------|------------|--|-----------------|-----------------|
| <b>Model</b>                                     | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| CMS-01X  | 65 X 90 X 35              | 2360       | NPN/PNP Type ,Sensing Distance : 4 to 8 mm   | 90329000        | 18%             |
| CMS-5X   | 28 X 60 X 44              | 5775       | NPN/PNP Type ,Sensing Distance : 10 to 15mm  |                 |                 |
| <b>Controller For Hydraulic Shearing Machine</b> |                           |            |  |                 |                 |
| <b>Model</b>                                     | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
| DRO-1102   | 96 X 96 X 50              | 7945       | Input : Dual Channel NPN Encoder + 230V AC Pulse for Home Position + 230V AC Pulse For Lock Reading<br>Output : 2 Relay for Forward - Reverse Operation of Motor<br>Supply : 230V AC | 90291090        | 18%             |
| LRO-1203   | 96 X 96 X 50              | 7515       | Input : 230V AC Pulse For Count + 230V AC Pulse from Limit Switch<br>Output : 2 Relay for Rack Up-Down Function, 1 Relay for set count ,<br>Supply : 230V AC                         |                 |                 |



**Power & Energy Meters**

## Single Phase Panel Meter

### Digital Ampere Meter

| Model   | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|---|--------------------|------|---|----------|----------|
| AV-14   | 96 X 96 X 42       | 1050 | Input : 0-5A AC Direct OR CT Selectable upto 5/5<br>To 4000/5A,<br>Supply : 230V AC | 90303310 | 18%      |
| AV-24   | 72 X 72 X 35       | 1050 |   |          |          |
| AV-34   | 48 X 96 X 58       | 1050 |   |          |          |
| AV-41CT   | 48 X 48 X 70       | 1195 |   |          |          |
| <b>Note : Direct upto 30A AC (Model : AC-11A, AV-21A, AV-31A, AV-41A)</b> |                    | 275  |   |          |          |

### Digital Volt Meter

| Model  | Size (H X W X D)mm | MRP | Item Description                       | HSN Code | GST Rate |
|--------|--------------------|-----|--|----------|----------|
| AV-11V | 96 X 96 X 42       | 930 | Input : 0-500V AC,<br>Supply : 230V AC | 90303310 | 18%      |
| AV-21V | 72 X 72 X 35       | 930 |  |          |          |
| AV-31V | 48 X 96 X 58       | 930 |  |          |          |
| AV-41V | 48 X 48 X 70       | 930 |  |          |          |

### Digital Ampere + Volt Meter

| Model                            | Size (H X W X D)mm | MRP        | Item Description  | HSN Code | GST Rate |
|----------------------------------|--------------------|------------|---|----------|----------|
| AV-12                            | 96 X 96 X 42       | 1290       | Input Volt : 0-500V AC,<br>Ampere : CT Ratio 5/5 to 2000/5A AC,<br>Supply : 230V AC | 90303310 | 18%      |
| AV-22                            | 72 X 72 X 50       | 1290       |   |          |          |
| AV-33                            | 48 X 96 X 58       | 1290       |   |          |          |
| <b>Note : Direct upto 30A AC</b> |                    | <b>275</b> |   |          |          |
| AV-44                            | 48 X 48 X 46       | 1710       | Input Volt : 0-500V AC,<br>Ampere :30.0 A Direct<br>Supply : 230V AC                |          |          |

| <b>Digital DC Ampere Meter</b>         |                    |      |  |          |          |
|--|--------------------|------|--|----------|----------|
| Model                                  | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| AV-14DZ                                | 96 X 96 X 42       | 1595 | Range : 0-20.0A DC Direct,<br>Supply : 230V AC   | 90303310 | 18%      |
| AV-24DZ                                | 72 X 72 X 35       | 1595 |  |          |          |
| AV-34DZ                                | 48 X 96 X 58       | 1595 |  |          |          |
| <b>Digital DC Ampere Meter</b>         |                    |      |  |          |          |
| Model                                  | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| AV-14DA                                | 96 X 96 X 42       | 1155 | Range : Multirange 0001 to 9999A DC Selectable,<br>Input : 0 to 75mV DC (through shunt),<br>Supply : 230V AC                   | 90303310 | 18%      |
| AV-24DA                                | 72 X 72 X 35       | 1155 |  |          |          |
| AV-34DA                                | 48 X 96 X 58       | 1155 |  |          |          |
| Note : Shunt in Customers Scope        |                    |      |  |          |          |
| <b>Digital DC Volt Meter</b>           |                    |      |  |          |          |
| Model                                  | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| AV-14DV                                | 96 X 96 X 42       | 1155 | Input Range : 19.99V DC / 49.99V DC / 99.99V DC<br>/ 199.9V DC / 750V DC(Factory set),<br>Supply : 230V AC                     | 90303310 | 18%      |
| AV-24DV                                | 72 X 72 X 35       | 1155 |  |          |          |
| AV-34DV                                | 48 X 96 X 58       | 1155 |  |          |          |
| AV-41DV (3 Digit)                      | 48 X 48 X 70       | 1155 |  |          |          |
| <b>Digital DC Amp &amp; Volt Meter</b> |                    |      |  |          |          |
| Model                                  | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| VAW-34DC                               | 48 X 96 X 58       | 2125 | Current Range : Multirange 0001 to 9999A DC<br>Selectable,<br>Voltage range : 750V DC,Watt : Up to 7499 KW<br>Supply : 230V AC | 90303310 | 18%      |
| <b>Single Phase Frequency Meter</b>    |                    |      |  |          |          |
| Model                                  | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
| FRQ-11                                 | 96 X 96 X 42       | 1055 | Range : 45.0 to 65.0Hz,<br>Supply : 230V AC  | 90303390 | 18%      |
| FRQ-21                                 | 72 X 72 X 35       | 1055 |  |          |          |
| FRQ-31                                 | 48 X 96 X 58       | 1055 |  |          |          |

### Single Phase Watt Meter

| Model | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-------|--------------------|------|---|----------|----------|
| WM-11 | 96 X 96 X 42       | 2645 | Range : 0 to 1250Watt (4 Digit, Range : 0 to 1250Watt, CT Selectable upto 50A),<br>Supply : 230V AC | 90303390 | 18%      |

### Single Phase KWh Meter

| Model | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-------|--------------------|------|--|----------|----------|
| EM-1P | 96 X 96 X 52       | 2090 | 6 Digit Active Energy (KWh), CT Ratio Selectable upto 5/5 to 4000/5A AC,<br>Supply : 230V AC | 90283090 | 18%      |

### Single Phase Power Factor Meter

| Model | Size (H X W X D)mm | MRP  | Item Description                                     | HSN Code | GST Rate |
|-------|--------------------|------|--|----------|----------|
| PF-11 | 96 X 96 X 42       | 1100 | Single Phase Power factor meter,<br>Supply : 230V AC | 90303390 | 18%      |

### Three Phase Power Factor Meter

| Model | Size (H X W X D)mm | MRP  | Item Description                                    | HSN Code | GST Rate |
|-------|--------------------|------|---|----------|----------|
| PF-13 | 96 X 96 X 42       | 2475 | Three Phase Power factor meter,<br>Supply : 230V AC | 90303390 | 18%      |

# Three Phase Energy & Power Meters

## Three Phase Energy (KWh) Meter

| Model                                     | Size (H X W X D)mm | MRP         | Item Description  | HSN Code | GST Rate |
|---|--------------------|-------------|---|----------|----------|
| EM-10                                     | 96 X 96 X 52       | 2425        | 6 Digit Active Energy (KWh),<br>CT Ratio Selectable upto 5/5 to 4000/5A AC,<br>Supply : 230V AC   | 90283090 | 18%      |
| EPM-14                                    | 96 X 96 X 52       | 3450        | CT Ratio Selectable upto 5/5 to 6000/5A AC,<br>6 + 4 Digit, 2 Line LED Display(6 Digit Active<br>Energy (KWh) and 4 Digit Active Power (KW),<br><b>Pulse Output</b><br>Supply : 100-270V AC | 90283090 | 18%      |
| <b>Options In EPM-14N : RS-485 Modbus</b> |                    | <b>1050</b> |   |          |          |
| <b>1 Setpoint With Relay Output on KW</b> |                    | <b>725</b>  |   |          |          |

## Three Phase Ampere & Volt Meter

| Model   | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|---------|--------------------|------|--|----------|----------|
| AMP-23  | 72 X 72 X 50       | 1375 | 4 Digit 1 line Display,<br>CT Ratio Selectable upto 0 to 6000/5A AC, Supply :<br>100-270V AC   | 90303390 | 18%      |
| AMP-13  | 96 X 96 X 42       | 1375 |  |          |          |
| VOLT-23 | 72 X 72 X 50       | 1460 | 4 Digit 1 line Display,<br>Primary PT : 100 to 999Kv AC(L-L)                                   |          |          |
| VOLT-13 | 96 X 96 X 42       | 1460 | Secondary PT : 100 to 520V AC(L-L),<br>Supply : 230V AC  |          |          |
| VOLT-19 | 96 X 96 X 42       | 1935 | 3 Digit 3 line Display,<br>Range : 50 - 500V AC(P-P), 30-300V AC (P-N)<br>Supply : 100-270V AC |          |          |
| AMP-19  | 96 X 96 X 42       | 2075 | 3 Digit 3 Line Display,<br>CT Ratio Selectable upto 0 to 6000/5A AC,<br>Supply : 230V AC       |          |          |

| <b>AVF Meter</b>  |                           |             |   |                 |                 |
|---|---------------------------|-------------|---|-----------------|-----------------|
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| AVF-19D   | 96 X 96 X 52              | 1980        | CT Ratio Selectable upto 6000/5A AC,<br>3 Phase /1 Phase Selection,<br>Supply : 230V AC   | 90303390        | 18%             |
| AVF-29T   | 72 X 72 X 45              | 2070        | CT Ratio Selectable upto 6000/5A AC,<br>3 Phase /1 Phase Selection,<br>Supply : 100-270V AC   |                 |                 |
| AVF-133 (6 Display)   | 96 X 96 X 52              | 2250        | CT Ratio Selectable upto 10000/5A AC,<br>3 Phase / 1 Phase Selection,<br>Supply : 100-270V AC   | 90303390        | 18%             |
| <b>Single Phase Current Controller</b>  |                           |             |   |                 |                 |
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| CC-12 (Double Display)  | 96 X 96 X 52              | 3290        | Current Range : 5A to 2000A AC,(1CT Input)<br>Output -1 Relay<br>Supply : 100 -270V AC  | 85363000        | 18%             |
| <b>Additional one relay available in CC-122</b>                               |                           | <b>725</b>  |   |                 |                 |
| <b>Motor Protection Device</b>  |                           |             |   |                 |                 |
| <b>3 Digit 3 Line, Red Display, 3 Phase Current Indication &amp; Tripping</b> |                           |             |   |                 |                 |
| <b>Model</b>  | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| MPD-192   | 96 X 96 X 52              | 3665        | CT Ratio Selectable Upto 5/5 to 6000/5A AC,<br>3 Phase 3 Wire / 4 Wire Selectable,<br>Output : 1 Relay for tripping parameters,<br>Tripping Facility : Over voltage, Under voltage, Over<br>current , Under current, Unbalance, SPP, Phase<br>sequence, Over frequency, Under frequency,<br>Neutral loss, Short circuit, Lock rotor point ,<br>Supply : 100-270V AC | 85363000        | 18%             |
| <b>With ELR Function (MPD-19EL)</b>   |                           | 4655        |   |                 |                 |
| <b>With Din 30AX CT Module (3 CT)- 30Amp</b>                                  |                           | <b>1075</b> |   |                 |                 |
| <b>With Din 60AX CT Module (3 CT)- 60Amp</b>                                  |                           | <b>1320</b> |   |                 |                 |
| <b>with supply : 415V AC</b>  |                           | <b>425</b>  |   |                 |                 |
| <b>RS-485 MODBUS (MPD-19EL -M1)</b>   |                           | 6250        |   |                 |                 |
| MPD-152 (Din rail -55mm)  | 75 X 55 X 110             | 2640        |   |                 |                 |

## Voltage & Current Protection Relay (Din rail)

| Model  | Size (H X W X D)mm | MRP         | Item Description  | HSN Code | GST Rate |
|--|--------------------|-------------|---|----------|----------|
| VPR-126                                      | 75 X 45 X 110      | 2145        | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 1 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 100-270V AC | 85363000 | 18%      |
| VPR-126-2R                                   | 75 X 45 X 110      | 2425        | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 2 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 100-270V AC |          |          |
| VPR-3P                                       | 75 X 45 X 110      | 1980        | Voltage Range : 50 to 520V AC (P-P),<br>Output : 2 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency,<br>Supply : Self Powered                                |          |          |
| CPR-30                                       | 70 X 55 X 65       | 1550        | Current Range : 5A to 30A AC(3CT)<br>Tripping Facility : Over Current , Under Current,<br>Output -1 Relay<br>Supply : 230V AC   |          |          |
| CPR-126-1C                                   | 75 X 45 X 110      | 1760        | Current Range : 0 to 999A AC,(1CT Input)<br>Tripping Facility : Over Current , Under Current,<br>Asmmetry,Output -1 Relay<br>Supply : 100 -270V AC  |          |          |
| <b>With 30A Single CT</b>                    |                    | <b>360</b>  |   |          |          |
| <b>With 60A Single CT</b>                    |                    | <b>450</b>  |   |          |          |
| CPR-126-3C                                   | 75 X 45 X 110      | 2175        | Current Range : 0 to 999A AC,(3CT Input)<br>Tripping Facility : Over Current , Under Current,<br>SPP, Asmmetry,Output -1 Relay<br>Supply : 100 -270V AC   |          |          |
| <b>With Din 30AX CT Module (3 CT)- 30Amp</b> |                    | <b>1075</b> |   |          |          |
| <b>With Din 60AX CT Module (3 CT)- 60Amp</b> |                    | <b>1320</b> |   |          |          |

|                                       |                  |      |  |          |     |
|---------------------------------------|------------------|------|--|----------|-----|
| CPR-22                                | 90 X 22.5 X 67.5 | 1295 | Current Range : 100mA to 5A AC(1CT Input)<br>Tripping Facility : Over Current , Under Current,<br>Output -1 Relay<br>Supply : 100 -270V AC   | 85363000 | 18% |
| VPR-22                                | 90 X 22.5 X 67.5 | 1320 | Voltage Range : 280 to 520V AC (P-P),<br>Output : 1 Relay<br>Tripping Facility : Over voltage, Under voltage,<br>Phase asymmetry, Phase loss, Phase sequence<br>Supply : Self Powered  |          |     |
| VPR-22U                               | 90 X 22.5 X 67.5 | 1520 | Voltage Range : 280 to 520V AC (P-P),<br>Output : 1 Relay<br>Tripping Facility : Over voltage, Under voltage,<br>Phase asymmetry, Phase loss, Phase<br>sequence, <b>With Selectable Trip Delay Time</b><br>Supply : Self Powered |          |     |
| SPP-22-1<br>(Single Phase preventor ) | 90 X 22.5 X 67.5 | 770  | Voltage Range : 280 to 520V AC (P-P),<br>Output : 1 Relay<br>Tripping Facility : Phase asymmetry, Phase Loss,<br>Supply : Self Powered   |          |     |
| SPP-22<br>(Single Phase preventor )   | 90 X 22.5 X 67.5 | 770  | Voltage Range : 280 to 520V AC (P-P),<br>Output : 1 Relay<br>Tripping Facility : Phase asymmetry, Phase Loss,<br>Phase sequence,<br>Supply : Self Powered  |          |     |
| V22-RYB<br>(Single Phase preventor )  | 90 X 22.5 X 67.5 | 835  | Voltage Range : 280 to 520V AC (P-P),<br>Output : 1 Relay<br>Tripping Facility : Phase asymmetry, Phase Loss,<br>Phase sequence,<br>Supply : Self Powered  |          |     |

## Voltage & Current Protection Relay - Panel Mounted

| Model   | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|---------|--------------------|------|---|----------|----------|
| VMR-132 | 96 X 96 X 52       | 2695 | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 2 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 100-270V AC | 85363000 | 18%      |
| VMR-13  | 96 X 96 X 52       | 2340 | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 1 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 100-270V AC |          |          |
| VMR-232 | 72 X 72 X 45       | 2695 | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 2 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 50-520V AC  |          |          |
| VMR-23  | 72 X 72 X 45       | 2340 | Voltage Range : 30 to 300V AC (P-N) / 50 to 520V AC (P-P),Output : 1 Relay<br>Tripping Facility : Over voltage, Under voltage, Phase asymmetry, SPP, Phase sequence, Over frequency, Under frequency, Neutral loss,<br>Supply : 50-520V AC  |          |          |
| CPR-19  | 96 X 96 X 52       | 2970 | CT Ratio Selectable Upto 5/5 to 9999/5A AC,<br>Output : 1 Relay for tripping parameters,<br>Tripping Facility : Over current , Under current, Unbalance, SPP, Short circuit, Lock rotor point ,<br>Supply : 100-270V AC                     |          |          |



| <b>Earth to Neutral Voltage Relay</b>        |                           |             |   |                 |                 |
|--|---------------------------|-------------|---|-----------------|-----------------|
| <b>Model</b>                                 | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| EN-19N                                       | 96 X 96 X 52              | 3600        | Input : 10.00V AC,<br>Output : 1 Relay for Tripping,<br>Supply : 230VAC | 85363000        | 18%             |
| <b>Options : RS-485 MODBUS Communication</b> |                           | <b>1050</b> |   |                 |                 |

| <b>Earth Leakage Relay With CBCT</b>      |                           |             |   |                 |                 |
|---|---------------------------|-------------|---|-----------------|-----------------|
| <b>Model</b>                              | <b>Size (H X W X D)mm</b> | <b>MRP</b>  | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
| ELR-19N                                   | 96 X 96 X 52              | 2640        | Input : 30mA to 3.00A AC through External CBCT,<br>Output : 1 Relay for Tripping,<br>Supply : 100-250V AC | 85363000        | 18%             |
| ELR-63 (Din rail)                         | 76 X 28 X 85              | 1980        |   |                 |                 |
| <b>Options : RS-485 MODBUS In ELR-19N</b> |                           | <b>1050</b> |   |                 |                 |
| CBCT Avilable 35mm, 70mm,120mm,210mm      |                           |             |   |                 |                 |
| EFR-63                                    | 76 X 28 X 85              | 1980        | Input : 5AMP through External CBCT,<br>Output : 1 Relay for Tripping,<br>Supply : 100-250V AC             |                 |                 |

# Multifunction Meters

## DC Multifunction Meter

| Model                                | Size (H X W X D)mm | MRP  | Item Description                                    | HSN Code | GST Rate |
|--------------------------------------|--------------------|------|---|----------|----------|
| MFM-14DC Meter                       | 96 X 96 X 52       | 3520 | Parameters: Volt, Amp, Watt & KWH, Supply : 230V AC | 90283090 | 18%      |
| Option : RS-485 Modbus Communication |                    | 1050 |   |          |          |

Note : Confirm the Voltage & Ampere range while order

## Single Phase Multifunction Meter

| Model                                | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|--------------------------------------|--------------------|------|---|----------|----------|
| PM-11H AC meter                      | 96 X 96 X 52       | 2860 | Parametrs : Active & Apparent Power, Active Energy, Power Factor, Volt, Ampere & Frequency,Supply : 230V AC | 90283090 | 18%      |
| Option : RS-485 Modbus Communication |                    | 1050 |   |          |          |

## Three Phase Multifunction Meter

| Model                                | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|--------------------------------------|--------------------|------|---|----------|----------|
| MFM-13                               | 96 X 96 X 52       | 3900 | 4 digit 3Line Red LED Display,<br>CT Ratio Selectable upto 5/5 to 6000/5A AC,<br>Parameters : P-P Voltage, P-N Voltage, Phase Current, Active Power(KW), Energy (KWh), Power Factor(PF) , Apparent Power (KVA), Reactive Power(KVAr), Frequency<br>Supply : 100-270V AC   | 90283090 | 18%      |
| AVH-14                               | 96 X 96 X 52       | 4070 | 6 digit 1 Line, 4 Digit 3 Line Red LED Display,<br>CT Ratio Selectable upto 5/5 to 6000/5A AC,<br>Parameters : P-P Voltage, P-N Voltage, Phase Current, Active Power (KW) (Per Phase & Average), Energy (KWh), Power Factor (PF) Per Phase & Average, Apparent Power (KVA), Reactive Power (KVAr), Frequency (F),<br>Supply : 100-270V AC | 90283090 | 18%      |
| Option : RS-485 Modbus Communication |                    | 1050 |   |          |          |

### Automatic Power Factor Controller up to 16 Stage

| Model    | Size (H X W X D)mm | MRP   | Item Description  | HSN Code | GST Rate |
|----------|--------------------|-------|---|----------|----------|
| APFC-108 | 144 X 144 X 55     | 8775  | Input : 2 Phase Voltage, 1 Phase CT,<br>Output : 8 /12/14/16 Output | 85363000 | 18%      |
| APFC-112 |                    | 10175 |   |          |          |
| APFC-114 |                    | 12375 |   |          |          |
| APFC-116 |                    | 14460 |   |          |          |

### Automatic Power Factor Controller: 6 Stage

| Model                             | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|-----------------------------------|--------------------|------|---|----------|----------|
| APFC-9606                         | 96 X 96 X 70       | 6870 | Input : 2 Phase Voltage, 1 Phase CT,<br>Output : 6 Relay,Supply : 230V AC | 85363000 | 18%      |
| APFC-96L6 (Graphical LCD Display) | 96 X 96 X 70       | 7250 |   | 85363000 | 18%      |

### AC-DC Testing Panel

| Model  | MRP   | Item Description  | HSN Code | GST Rate |
|--|-------|---|----------|----------|
| AC-DC -15A                                   | 11000 | 4 digit + 4 Line, 4 Digit 3 Line Red LED Display,<br><b>Parameters</b> : AC Parameters : Ampere, Voltage, Power Factor, Watt<br>DC Parameters : Ampere, Voltage, Efficiency, Watt,<br>Supply :230V AC | 90283090 | 18%      |
| <b>Options : RS-485 Modbus Communication</b> |       | <b>1050</b>   |          |          |

## Multi Channel Current Transducer

| Model     | Size (H X W X D)mm | MRP  | Item Description   | HSN Code | GST Rate |
|-----------|--------------------|------|--|----------|----------|
| MCS-360   | 76 X 28 X 1116     | 2350 | Input Current : 1A to 60A (3CT),<br>Output : Modbus,<br>Supply : 24V DC  | 90329000 | 18%      |
| MCS-460   |                    | 2850 | Input Current : 1A to 60A (4CT),<br>Output : Modbus,<br>Supply : 24V DC  |          |          |
| MCS-660   |                    | 3750 | Input Current : 1A to 60A (6CT),<br>Output : Modbus,<br>Supply : 24V DC  |          |          |
| MCS-3-100 |                    | 3350 | Input Current : 4A to 100A (3CT),<br>Output : Modbus,<br>Supply : 24V DC |          |          |

## Water Level Controller

| Model         | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|---------------|--------------------|------|---|----------|----------|
| WLC-22        | 90 X 22.5 X 67.5   | 1375 | Sensitivity : Up to 200K Ohm<br>Output : 1R1C/O<br>Supply : 100-270V AC | 90328910 | 18%      |
| Probe for WLC |                    | 330  |   |          |          |

**DC Drives****Panel Mounted**

| <b>Model</b> | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>   | <b>HSN Code</b> | <b>GST Rate</b> |
|--------------|---------------------------|------------|---|-----------------|-----------------|
| TD-144       | 140 X 140 X190            | 4960       | 0.5 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 3A DC<br>Supply : 230V AC  | 85044029        | 18%             |
| TD-144       | 140 X 140 X190            | 5270       | 1.0 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 5A DC<br>Supply : 230V AC  |                 |                 |
| TD-144       | 140 X 140 X190            | 6450       | 2.0 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 10A DC<br>Supply : 230V AC |                 |                 |
| TD-144       | 140 X 140 X190            | 6690       | 3.0 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 15A DC<br>Supply : 230V AC |                 |                 |

**Wall Mounted**

| <b>Model</b> | <b>Size (H X W X D)mm</b> | <b>MRP</b> | <b>Item Description</b>  | <b>HSN Code</b> | <b>GST Rate</b> |
|--------------|---------------------------|------------|--|-----------------|-----------------|
| TD-13M       | 170 X 235 X 85            | 3650       | 0.5 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-220V DC<br>Output Current : 3A DC<br>Supply : 230V AC | 85044029        | 18%             |
| TD-13M       | 170 X 235 X 85            | 4290       | 1 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-220V DC<br>Output Current : 5A DC<br>Supply : 230V AC   |                 |                 |
| TD-13M       | 210 X 285 X 110           | 5220       | 2 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-220V DC<br>Output Current : 10A DC<br>Supply : 230V AC  |                 |                 |
| TD-13M       | 210 X 285 X 110           | 5510       | 3 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-220V DC<br>Output Current : 15A DC<br>Supply : 230V AC  |                 |                 |
| TD-13M       | 210 X 285 X 110           | 7080       | 5 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-220V DC<br>Output Current : 15A DC<br>Supply : 230V AC  |                 |                 |

### Box Type, Wall Mounted With Start / Stop Push Button

| Model  | Size (H X W X D)mm | MRP  | Item Description  | HSN Code | GST Rate |
|--------|--------------------|------|---|----------|----------|
| TD-13B | 160 X 240 X95      | 5435 | 0.5HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 3A DC<br>Supply : 230V AC | 85044029 | 18%      |
| TD-13B | 160 X 240 X95      | 5935 | 1 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 5A DC<br>Supply : 230V AC  |          |          |
| TD-13B | 230 X 300 X 105    | 7435 | 2 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 10A DC<br>Supply : 230V AC |          |          |
| TD-13B | 230 X 300 X 105    | 8295 | 3 HP<br>Field Voltage : 210V DC<br>Armature Voltage : 20-200V DC<br>Output Current : 15A DC<br>Supply : 230V AC |          |          |

### MFM Panel

### Three Phase Multifunction Meter With Panel

| Model     | Load Upto   | MRP   | Item Description  | HSN Code | GST Rate |
|-----------|-------------|-------|---|----------|----------|
| MFM Panel | 30A Direct  | 10455 | 6 digit 1 Line, 4 Digit 3 Line Red LED Display,<br>Parameters : P-P Voltage, P-N Voltage, Phase<br>Current, Active Power (KW) (Per Phase &<br>Average), Energy (KWh), Power Factor(PF) Per<br>Phase & Average, Apparent Power (KVA), Reactive | 90283090 | 18%      |
|           | 60A Direct  | 11555 |   |          |          |
|           | 100A Direct | 12115 |   |          |          |

## Customised Products

| Model                     | Size (H X W X D)mm | MRP   | Item Description   | HSN Code | GST Rate |
|---------------------------|--------------------|-------|--|----------|----------|
| FDI-100 (Flame Proof)     | 142 X 142 X 86     | 5871  | Temperature Indicator ,Fixed Input   | 90328910 | 18%      |
| FRI-100 (Flame Proof)     | 142 X 142 X 86     | 5871  | Input: Proximity,<br>Supply : 24V DC   | 90291090 | 18%      |
| MDT-3006                  | 48 X 96 X 120      | 6099  | 2 Input & 2 Output (Jumping Timer)   | 85369090 | 18%      |
| MI-631                    | 76 X 27 X 116      | 4007  | Input : 1K Pot (3Wire),<br>Output : 4 To 20 mA,<br>Supply : 230V AC  | 90303390 | 18%      |
| MPC-5356                  | 96 X 192 X 130     | 24710 | Length Counter,<br>Input : Encoder, 24 V DC Supply, With 0 TO 10 V<br>DC, PID O/P, Reset at back   | 90291090 | 18%      |
| MPC-5356                  | 96 X 192 X 130     | 24710 | Length Measurement,<br>Upper : 99999 Count,<br>Lower : MT/MIN,<br>Input : Encode & 0 - 10 VDC,<br>Supply : 230 V AC, Reset at Back, 2 Relay Output | 90291090 | 18%      |
| MPC-5356                  | 96 X 192 X 130     | 23011 | Traverse Measurement,<br>Upper : 9999.9 Count,<br>Input : Encoder,<br>Supply : 230 V AC, Reset at back, 3 Relay O/P.                               | 90291090 | 18%      |
| MTC-1201                  | 96 x 96 x 50       | 7667  | Input : 0 TO 1000 V DC,<br>Output : 1 Relay (For Tripping),<br>Hy. : 0- 99 Selectable,<br>Supply : 230 V AC (Linear),<br>Enter at back,            | 90328910 | 18%      |
| FA-11 (Fault Annunciator) | 96 x 96 x 52       | 10226 | 16 x 2 Characters LCD Display<br>10 Input and 3 Output(Audio, Visual & Machine<br>Tripping)  | 90303390 | 18%      |
| SPI-2044                  | 72 x 72 x 60       | 4589  | Speed Indication with Pulse Input  | 90303390 | 18%      |
| SPI-4044                  | 48 x 48 x 95       | 4589  | Speed Indication with Pulse Input  | 90303390 | 18%      |
| RC-2006                   | 72 x 72 x 60       | 17699 | Haul Off Controller  | 90291090 | 18%      |



|                               |               |      |  |          |     |
|-------------------------------|---------------|------|--|----------|-----|
| PIC-410A                      | 48 x 48 x 95  | 3363 | Current / Voltage Source   | 90303390 | 18% |
| SPI-21                        | 72 x 72 x 50  | 2622 | Process Indicator  | 90303390 | 18% |
| FSC-1006                      | 96 x 96 x 100 | 4691 | Fill Seal Controller<br>Input : Proximity NPN/PNP<br>Output : 2 SSR + BUZZER   | 90291090 | 18% |
| MMC-1340                      | 96 x 96 x 52  | 9012 | Programmable Counter<br>Input : Proximity NPN / PNP (24V DC)<br>Output : Relay + SSR   | 90291090 | 18% |
| RTC 223PX                     | 72 X 72 X 60  | 7934 | Temperature Controller with ampere (2 Line Display)  | 90328910 | 18% |
| RTC 2303-1C                   | 72 X 72 X 60  | 9833 | Temperature Controller with ampere (3 Line Display)  | 90328910 | 18% |
| MMC-1048                      | 96 x 96 x 50  | 7701 | Total Count & Speed Indicator<br>8 Digit Total Count, 4 Digit RPM<br>Input : NPN/PNP Proxi Selectable<br>Output : 1 Relay 1C/O (ON TOTAL COUNT), RS-485 (MODBUS) | 90291090 | 18% |
| MH-200P(Hooter)               | 96 x 96 x 50  | 1197 | Panel Mounting Hooter<br>Input Voltage : 230V AC Or 24V DC   | 85311090 | 28% |
| MH-200W (Hooter)              | 96 x 96 x 50  | 1197 | Wall Mounting Hooter<br>Input Voltage : 230V AC Or 24V DC  | 85311090 | 28% |
| MTC-1203                      | 96 x 96 x 50  | 4452 | Input : J/K/Pt-100(Factory set)<br>Output : 3 Relay (Heating /Cooling Factory set)<br>Supply : 100-250V AC   | 90328910 | 18% |
| <b>Terms &amp; Conditions</b> |               |      |  |          |     |

1. Above prices are Ex-Works State & Central Taxes inclusive.
2. Packing and forwarding charges will be extra as applicable.
3. Warranty : 12 Months from the date of invoice against any manufacturing defects.
4. Any additional customization in terms of features would be charged extra.
5. Visit charges of engineer for installation or repairing would be charged extra.
6. Charges for internal laboratory calibration report will be applicable extra.
7. The above prices are subject to change without any notice as per raw material cost changes & labour cost charges.
8. Order cancellation charges for stock products will be 10% of the order value.
9. Order for customized products will be against advance only and once placed cannot be cancelled.
10. Subject to Ahmedabad jurisdiction.

